

OC85 SLIDING FIRE DOORS

OCEAN

Certified interior glass partition systems for cruise ships




SKANDI·BO® 

OCEAN OC85 Interior sliding fire doors

The SKANDI-BO OCEAN OC85 Sliding Fire Doors are available as single leaf and double leaf framed glass sliding doors MED/EC classified as BO-B15 & FRD60 for HSC.

Advantages:

- Extremely slim aluminium profile design
- Lowest possible weight in the market
- The doors are certified without threshold allowing continuous flooring design from room to room
- Easy and fast installation to bulkhead by welding or screws



Specifications

- Aluminium profile system SKANDI-BO OC85 in standard RAL colours or anodized
- Manual operation or automation according to customer specification.
- 16 mm respective 27 mm fire resistant glass

Door type	Class	Max Clear opening		Kgs/m ² *	DNV MED Certificate no.
		Width mm	Height mm		
Single Leaf	BO - B15 (B30)	1385	2445	69	MED-B-00000CU
Double Leaf Asymmetric	BO - B15 (B30)	2340	2500	69	MED-B-00006NE
Double Leaf Symmetric	BO - B15 (B30)	1950	2500	69	MED-B-00006NE
Double Leaf Symmetric	FRD60 for HSC	2420	2270	96	PGA11224

*Weight incl. standard fire protective glass, excl. automation

Design options

- Certified with side partitions allowing the sliding door to be integrated as a part of a larger glass partition wall
- Symmetric as well as asymmetric door leaf sizes
- Special colours and other surface finishes on the aluminium profiles are possible
- Fire protective glass combined with function glass, decoration or noise reduction improving glass as an option.
- Automation and remote operation control are optional
- New in the market: FRD60 as double sliding doors with full framed glass

Contact marine sales

SKANDI-BO A/S

www.skandi-bo.dk

ars@skandi-bo.dk

+45 27742272

SKANDI-BO® 